

### Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KW 012 - PES - MATT FLAG FABRIC	
<b>Application</b>	Banner / Flags / Beach Flags	
<b>Printable Ink</b>	Treatment applied for Sub Paper , Direct Sub., Latex, Uv-Curable	
<b>Material</b>	100 % Polyester	
<b>Standart Sizes</b>	App.103cm,205cm,260cm,310cm (40",80",102",122") x 100mt.(109 yrd.)	
<b>Weight</b>	110 ( g/m2 )+- 5(gr) (3,8 oz)	
<b>Tensile Strength</b>	38/84 warp/weft (daN)	DIN EN ISO 13934-1
<b>Tear Resistance</b>	37/45 warp/weft (N)	DIN EN ISO 13937-4
<b>Finishing</b>	Digital Coating	
<b>Packaging</b>	3" paper core, wrapped with stretch film + put in a cardboard box	

Our product enables to have vivid colors and good printing quality with SUB., LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink Type



Sub Direct and Paper Transfer



UV Printable



Latex Printable



Fire Retardant



Fire Retardant



Fire Retardant



European Standard



Cutting



Cold Cut

\*Optional



Be Green ♻️



All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.