

Lona Doble Cara Blockout 1000*1000 20*20 610gr

Flexible PVC banner is suitable for all solvent-based inkjet system. The special surface coating optimizes ink adhesion and color reproduction for long-lasting brilliant prints. After special treatment, PVC flex banner have a good capability of anti-microbial and anti-aging. PVC Coated banner is a quality choice for long-term outdoor advertising, such as large format signage, outdoor billboard and displays.

| Item | Product | Base Fabric | Weight (g/m ²) | Width |
|-----------|---|---------------------------|----------------------------|--------|
| CDM11/610 | PVC Coated banner Double sides print | 1000*1000D 20*20/sq.in | 610 | 1~3.2m |

Features:

1. Coating technology.
2. Outstanding tearing & peeling strength and very smooth surface.
3. Temperature resistance: -15~70 °C.
4. At least 1 year outdoor use.

Application:

1. Billboard.
2. Exhibition booth decoration
3. Displays (indoor and outdoor)..
4. Building murals and instore displays
5. Highway advertising

* Optional treatment (such as Fire Retardant, Anti-UV, Anti-cold) needs additional cost.

Physical Properties

| | | |
|----------------------|-------------------------|--------------------|
| Item code: | CDM11/610 | |
| Base fabric: | 1000D*1000D 20*20/sq.in | / |
| Weight | 610g/sqm | DIN53352 |
| Tensile | 2600N/5cm | DIN53354 |
| Strength(L): | | |
| Tensile Strength(W): | 2250N/5cm | DIN53354 |
| Tearing Strength(L): | 370N/5cm | DIN53363 |
| Tearing Strength(W): | 320N/5cm | DIN53363 |
| Peeling | 100N/5cm | DIN53363 |
| Strength(L): | | |
| Peeling Strength(W): | 100N/5cm | DIN53363 |
| Temperarue: | -15~70 °C | DIN53372 |
| Fire Retardant | Normal | Normal/B1/B2/M1/M2 |