Ficha técnica



Lona Fundida front lit Semi Mate Whit/Black mate 1000*1000D 16*16 440gsm

UNISIGN™ Flexible PVC banner is suitable for all solvent-based inkjet system. The special surface coating optimizes ink adhesion and color reproduction for long-lasting brilliant prints. After special treatment, UNISIGN™ PVC flex banner have a good capability of anti-microbial and anti-aging. UNISIGN™ PVC Coated banner is a quality choice for long-term outdoor advertising, such as large format signage, outdoor billboard and displays.

Item	Product	Base Fabric	Weight (g/m²)	Width
CFM11/440	PVC Coated banner	1000*1000D	440	1~5.1m
	r ve coated baille	16*16/sa in		

Features:

1. Coating technology. 2. Outstanding tearing & peeling strength and very smooth surface.

3. Temperature resistance: -15~70 °C.

4. At least 1 year outdoor use.

Application:

- 1. Billboard.
- 2. Exhibition booth decoration
- 3. Displays (indoor and
- outdoor)..
- 4. Building murals and instore displays
- 5. Highway advertising

Physical Properties

Item code:	CFM11/440	
Base fabric:	1000D*1000D 16*16/sq.in	/
Weight	440g/sqm	DIN53352
Tensile	2200N/5cm	DIN53354
Strength(L):		
Tensile Strength(W):	1900N/5cm	DIN53354
Tearing Strength(L):	300N/5cm	DIN53363
Tearing Strength(W):	250N/5cm	DIN53363
Peeling Strength(L):	90N/5cm	DIN53363
Peeling Strength(W):	90N/5cm	DIN53363
Temperarue:	-15 [~] 70°C	DIN53372
Fire Retardant	on request	Normal or B1/B2 or M1/M2/701



^{*} Optional treatment (such as Fire Retardant, Anti-UV, Anti-cold) needs additional cost.