

Technical Data Sheet

Issue date: 01/07/2014 Date last modification: 30/04/2018

# 4-GL3B-08313 RI-JET DECO-WALL 50 AP972 EXTRA PERMANENT GREY WKPE140 **AIRFLOW**

### Face Material

Gloss white CAST vinyl.

GRAPHICS -

Type CAST vinyl Colour and Finish Gloss white

ISO-536 Weight 70 g/m<sup>2</sup> ±10% ISO 534-80 **Thickness** 50 µ ±10%

#### Adhesive

Extra permanent adhesive with excellent adhesion on low energy surfaces (i.e. PP or PE containers). The adhesive has a very high peel adhesion and medium cohesion.

Reference AP972 extra permanent

Type Extra permanent

Min. Appl. Temp. +5°C Service Temp. -30/+120 C° Medium Shear

FINAT FTM9 Tack 10 N/25mm Final Adhesion 16 N/25mm FINAT FTM2

#### Liner

Embossed PE coated kraft paper Type

- Airflow texture

Colour and Finish White

PP-032 - ISO Weight 135 g/m<sup>2</sup> ±10% 536 ISO 534 **Thickness** 150 µ ±10% DIN 53 147-64 Transparency n.a. %

# **Applications**

3D conformable film for professional applications to brick walls, rough wall surfaces, painted household panels and similar substrates.

We advise an overlap of 1.5cm when positioning the decals.

Outdoor durability 5 years unprinted material

## **Printing Methods**

Printable with eco-solvent, solvent, UV and Latex ink-jet. Testing for suitability between media, printers and inks is always recommended prior to use.

#### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of  $22^{\circ}C \pm 2^{\circ}C$  and 50  $\pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



