


YD-R3200R5



More stable double negative ink supply system


Thermostatic cartridge system, keeping consistent ink viscosity

Anti-collision device

Easy material receiving design

Ricoh Gen5 industrial print head

Adopting new 2-8 pcs grey level Ricoh Gen5 internal heating industrial micro Piezo print head, 4-8 colors optional (6 color or 6+white and Varnish), variable drop printing (7pl-35pl), ink droplet is more intensive, multi-color printing, the colors are brighter, the printer can clearly print 2pt font, not only print with high resolution (up to 600x2400DPI), but also can print with high speed. What is more, working performance is stable, so it is very suitable for long-time working, 24 hours running. If maintained in good condition, the life time of print head can reach about 5 years.



Automatic material thickness measurement

Detect thickness of substrates automatically, no manual measurement required, precise, time-saving.



Humanized self-acting control design

The safety light curtains ensure obstacle free carriage moving, protecting the safety of users.

UV-LED curing lamp

Efficient UV-LED ink curing system, delivers more outstanding curing effect, energy-saving compared to mercury lamp, long service life up to 30000hrs.



Specification

Model	YD-R3200R5		
Print Head	Ricoh-Gen5 grey level piezo print head		
Number of heads	2-8pcs(4-8 colors optional)		
Print resolution	600×2400dpi		
Print speed	4 Pass	6 Pass	8 Pass
	38M ² /h(single row); 76M ² /h(double row)	29M ² /h(single row); 58M ² /h(double row)	22M ² /h(single row); 44M ² /h(double row)
Print width	3200mm(11ft)		
Material type	roll to roll material		
Material thickness	Up to 50mm(2in)		
Ink type	Eco-friendly UV curing ink (NO VOC), Disperse(Optional)		
Ink color	CMYK, Lc, Lm, W, V(Optional)		
RIP software	PhotoPrint		
Input format	PDF, JPEG, TIFF, EPS, AI		
Printer weight	2300KG		
Printer size	6600mm[L]×1500mm[W]×1600mm[H](21.6ft × 4.9ft × 5.2ft)		
Package size	6900mm[L]×1790mm[W]×1810mm[H](22.6ft × 5.9ft × 5.9ft)		
Power requirement	220V/AC (±10%) , 50 / 60 Hz, 6KW		
Working environment	Separate, little sunlight, ventilated workshop. Temperature:18° C ~ 30°C (64°F ~ 86°F) Humidity: 30% ~ 70% (Non-condensing) Ventilation equipment: Suggest Overhead exhaust fan, displacement 600 cfm		

Samples show

YD-R3200R5 roll to roll UV printer application:

Flexible materials: wall paper, advertising cloth, car sticker etc.



Outdoor advertising



Car sticker



PVC film