



cordón sellante / cordon d'etanchéité / sealing cord



italpanelli

Montaje aconsejado para asegurar la estanqueidad de la junta
 Montage conseillé pour assurer l'étanchéité de la joint
 Monting recommended to ensure the tightness of the seal

Aislante / Isolant / Insulation: Poliuretano / Polyuréthane / Polyurethane

Exterior / Extérieur / External: Chapa de acero prelacada / Tôle d'acier prélaquée / Prepainted steel

Interior / Intérieure / Internal: Chapa de acero prelacada / Tôle d'acier prélaquée / Prepainted steel

Pendiente mín./Pente min./Min. slope: 30%

Espesor / Épaisseurs / Thickness(mm):	60	80	100
K W/m²K:	0,383	0,288	0,230
K Kc/m²°C:	0,330	0,247	0,198
R m²K/W:	2,609	3,478	4,348

ESQUEMA ESTÁTICO - Distancia entre apoyos: cm.
 SCHÉMA STATIC - Distance entre les supports: cm.
 STATIC SCHEME - Distance between supports: cm.

Espesor del panel (mm)	Espesor Nominal		Peso	Distancia eficaz apoyos: 100 mm														
	exterior acero (mm)	exterior acero (mm)		150	175	200	225	250	275	300	325	350	375	400	425	450	475	500
60	0,50	0,50	9,9	375	320	280	250	200	165	140	120	100	90	75	70	60	55	50
80	0,50	0,50	10,7	455	390	340	300	260	215	180	150	130	115	100	90	80	70	60
100	0,50	0,50	11,5	530	455	395	350	310	255	215	180	155	135	120	105	95	85	75