Ficha técnica



Lámina Anti-graffiti AGI 100



DESCRIPTION

This anti-graffiti film is specially designed for easier cleaning of graffiti and protection of glass from deliberate attacks and scratches. ...

read More

Durability: from 12 to 15 years for vertical application in central

Use: Réflectiv window films are designed for use on any type of clear normal glass

Maintenance after 30 days: with usual cleaning solutions (non-abrasive, without ammonia...). Cleaning products that may scratch the film should be avoided.

Storage: 2 years from delivery. This film should be kept away from excessive humidity and sun rays, at temperatures below 38°C.

Application Method

The glass surface to be glued on has to be free from dust, grease or other contaminants. Some specific materials such as polycarbonate can cause air bubble problems. Therefore, a compatibility test is recommended. For more precision we recommend to refer back to the application table.

Production and standards

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice. Before applying our products we recommend that our users ensure that the film is suitable for the intended use and comply with current standards.

Material: PET 100 microns

Adhesive: acrylic polymer 17 gr/m² Liner: siliconized PET 23 microns

Color: Transparent

Application: Internal and external Breaking Load: 17,5 da N/cm Elongation at Break: 100% UVA Transmission: 5%

Application Temperature: min. + 5°C

Warranty:

10 years for application internal 5 years for application external

Fire Rating: B-s1,d0 Norms: Euroclasses Dimensions (of rolls):

1.52 x 2.5 m 1.52 x 10 m 1.52 x 30 m



